

## SPECIFICATIONS


DN mm	DN 50 - DN 300
DN inch	2" - 12 "
Temperature	70° NBR
Type of body	Flange
Application	Waste water
Flange	PN10/PN16
Norm	EN1092
Options	Other specifications on request



## ADVANTAGES


- The check valve includes a venting device to release the flap if it gets stuck due to backflow.
- Operating pressure of 10/16 bar.
- The check valve cover with NBR disc has an epoxy-coated body.
- It is mainly used in the infrastructure, municipal, and construction sectors, and is employed in various mechanical engineering, water treatment, and agricultural projects.

## NOMENCLATURE



Designation	Materials
1. Body	GGG40
2. Gasket	NBR
3. Disc	NBR
4. Cove seal	NBR
5. Cover	GGG40

## DIMENSIONS



DN mm	DN inch	PFA	D	D1	D2	L		F	H	B	N-d
						BS5153	DIN3202				
50	2"	10	165	125	102	203	200	3	118	19	4-19
65	2 1/2"	10	185	145	122	216	240	3	135	19	4-19
80	3"	10	200	160	138	241	260	3	160	19	8-19
100	4"	10	220	180	158	292	300	3	182	19	8-19
125	5"	10	250	210	188	330	350	3	205	19	8-19
150	6"	10	285	240	212	356	400	3	235	22	8-23
200	8"	10	340	295	268	495	500	3	275	22	12-23
250	10"	10	405	355	320	622	600	3	320	26	12-28
300	12"	10	460	410	378	698	700	3	365	26	12-28